

RUISKUOHENNE (Spray Thinner) 1032

Date 28.4.2008

Previous date: 17.6.2005

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- 1.1 Identification of the article**
- 1.1.1 Commercial Product Name**
RUISKUOHENNE (Spray Thinner) 1032
- 1.1.2 Product code**
006 1032
- 1.2 Use of the Substance/Preparation**
- 1.2.1 Intended use**
Painting work.
Description: Thinner
- 1.3 Identification of the company**
- 1.3.1 Supplier**
Tikkurila Oy
- 1.3.2 Contact information:**
- P.O.Box** P.O.Box 53
Postcode and post office FI-01301 VANTAA
FINLAND
- Telephone** +358 9 857 71
Telefax +358 9 8577 6936
- 1.3.4 Responsible for the Safety Data Sheet:**
Tikkurila Oy, Product Safety, e-mail: productsafety@tikkurila.com
- 1.4 Emergency telephone number**
- 1.4.1 Telephone number, name and address**
Tikkurila Oy, Environment and Safety: +358 9 857 71

2. HAZARDS IDENTIFICATION

Highly flammable, F
Harmful, Xn
Dangerous for the environment, N
Irritating to skin. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information on hazard labelling in section 15.1.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1	Hazardous components		3.1.2 Chemical name of the substance	3.1.3 Concentration	3.1.4 Classification
	3.1.1 CAS number	EINECS			
	64742-49-0	265-151-9	Naphtha, hydrotreated light (aliphatic hydrocarbon solvent)	100 %	F, Xn, N; R11-38-65-67-51/53

4. FIRST AID MEASURES

- 4.1 Additional advice**
In all cases of doubt, or when symptoms persist, seek medical attention.
- 4.2 Inhalation**
Remove to fresh air, keep patient warm and at rest.
- 4.3 Skin contact**
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser.

RUISKUOHENNE (Spray Thinner) 1032

Date 28.4.2008

Previous date: 17.6.2005

- 4.4 Eye contact**
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- 4.5 Ingestion**
If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

5. FIRE-FIGHTING MEASURES

- 5.1 Suitable extinguishing media**
Use foam, CO₂, powder or water spray.
- 5.2 Extinguishing media which must not be used for safety reasons**
Waterjet
- 5.3 Specific hazards**
Fire will produce dense black smoke, which contains decomposition products. Avoid breathing the smoke.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions**
Avoid breathing vapours. Exclude sources of ignition.
- 6.2 Environmental precautions**
Do not allow to enter drains or water courses.
- 6.3 Methods for cleaning up**
Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents.

7. HANDLING AND STORAGE

- 7.1 Handling**
Vapours are heavier than air and may form explosive mixtures with air. Good ventilation must be provided. Keep away from sources of ignition. Take precautionary measures against static discharges.
- 7.2 Storage**
Keep containers tightly closed. Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- 8.2 Exposure controls**
- 8.2.1 Occupational exposure controls**
Provide adequate ventilation. Comply with the health and safety at work laws.
- 8.2.1.1 Respiratory protection**
Use appropriate certified respirators, with gas and vapour filter A, during sanding with dust filter P2, if ventilation is insufficient. During spray-application use respirators with gas, vapour and dust filter AP. During continuous and long-term work the use of air-fed or motor-driven respirators is recommended.
- 8.2.1.2 Hand protection**
Always wear protective gloves (e.g. nitrile rubber). Barrier creams may also help to protect the exposed areas of the skin.
- 8.2.1.3 Eye protection**
Safety eyewear must be used, specially during spray-application.
- 8.2.1.4 Skin and body protection**
Protective clothing must be used during spray-application.

RUISKUOHENNE (Spray Thinner) 1032

Date 28.4.2008

Previous date: 17.6.2005

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1	General Information (appearance, odour) Liquid, strong odour	
9.2	Important Health Safety and Environmental Information	
9.2.2	Boiling point/range	87 - 110 °C
9.2.3	Flash point	< 0 °C
9.2.5	Explosive properties	
9.2.5.1	Lower explosion limit	1,4 vol-%
9.2.5.2	Upper explosion limit	7,6 vol-%
9.2.7	Vapour pressure	15 kPa (38 °C)
9.2.8	Relative density	0,72 - 0,75
9.2.9	Solubility	
9.2.9.1	Water solubility	Insoluble

10. STABILITY AND REACTIVITY

10.1	Conditions to avoid Solvent vapours may form explosive mixtures with air.
10.2	Materials to avoid Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
10.3	Hazardous decomposition products Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

11. TOXICOLOGICAL INFORMATION

11.1	Acute toxicity See section 11.5.
11.2	Primary irritation See section 11.5.
11.3	Sensitisation ---
11.5	Human experience 11.5.1 Inhalation: Solvent vapours and spray mist harmful if inhaled. Long term exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache and dizziness. 11.5.2 Skin contact: Repeated or prolonged contact with the preparation may cause removal of the natural fat from the skin resulting in contact dermatitis. Splashes in the eyes may cause irritation. 11.5.3 Other effects: Harmful if taken internally. The product contains solvent naphtha, which may cause lung damage if swallowed.

12. ECOLOGICAL INFORMATION

12.1	Ecotoxicity
12.1.1	Aquatic toxicity Naphtha, hydrotreated light: LL50 = 11 mg/l, fish, algae, daphnia magna; harmful
12.3	Persistence and degradability
12.3.1	Biodegradation Naphtha, hydrotreated light: readily biodegradable (estimate)
12.4	Bioaccumulative potential Naphtha, hydrotreated light: octanol/water partition coefficient log Kow = 2-7

RUISKUOHENNE (Spray Thinner) 1032

Date 28.4.2008

Previous date: 17.6.2005

12.6 Other adverse effects

There is no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

13.1 Product residues: Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).

13.2 Packaging waste: Empty cans should be recycled or disposed of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1	UN No	1268
14.2	Packing group	II
14.3	Land transport	
14.3.1	ADR/RID Class	3
14.3.3	Description of the goods	petroleum distillates, N.O.S. (naphtha, hydrotreated light)
14.4	Sea transport	
14.4.1	IMDG Class	3
14.4.2	Proper shipping name	petroleum distillates, N.O.S. (naphtha, hydrotreated light)
14.4.3	Further Information	EmS: F-E,S-E
14.5	Air transport	
14.5.1	ICAO/IATA Class	3
14.5.2	Proper shipping name	petroleum distillates, N.O.S. (naphtha, hydrotreated light)

15. REGULATORY INFORMATION

15.1	Information on the warning label	
	EC Label	265-151-9
15.1.1	Letter code of the warning symbol and indications of danger for the preparation	
	F	Highly flammable
	Xn	Harmful
	N	Dangerous for the environment
15.1.2	Names of the ingredients given on the warning label	
	Teollisuusbensiini, vetykäsitelty kevyt	
15.1.3	R-phrases	
	R11	Highly flammable.
	R38	Irritating to skin.
	R65	Harmful: may cause lung damage if swallowed.
	R67	Vapours may cause drowsiness and dizziness.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
15.1.4	S-phrases	
	S2	Keep out of the reach of children.
	S16	Keep away from sources of ignition - No smoking.
	S23	Do not breathe vapour/spray.
	S29	Do not empty into drains.
	S33	Take precautionary measures against static discharges.
	S51	Use only in well-ventilated areas.
	S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

RUISKUOHENNE (Spray Thinner) 1032

Date 28.4.2008

Previous date: 17.6.2005

16. OTHER INFORMATION**16.1 Full text of R-phrases referred to under sections 2 and 3**

R11	Highly flammable.
R38	Irritating to skin.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16.4 Additional information

The information of this MSDS is based on the present state of our knowledge and on current EC laws. It is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

Additional information available from: Tikkurila Oy, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND, Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com

Signature

a/akk