



Akrostop Stain Blocker

Description	Waterborne acrylate sealing paint. Prevents bleeding caused by nicotine, soot, liquid drawing ink and hides dried moisture damaged spots.
Product features	Single pack waterbased stain blocker suitable for use on both new and previously painted concrete, plaster, brick, putty, fibreboard, plasterboard, wood, panel and log surfaces. Akrostop is not suitable for use on iron or steel surfaces. Akrostop will not prevent the seepage of resin.

Do not mix the product with other products.

Recommended uses	Interior walls and ceilings
------------------	-----------------------------



TECHNICAL DATA



Colour Range	Tinted white
Gloss grade	Full-matt
Coverage	6-8 m ² /l depending on the substrate.
Can sizes	1, 3 and 10 L
Thinner	Water
Application method	Brush, roller or spray gun. Airless spray: - nozzle 0.015" 0.019" - thinning 0-10 vol %
Drying time at 23°C and 50% relative air humidity	Dust dry after 1 hour, recoatable after 6 hours.
Chemical resistance	Resists cleaning detergents and weak solvents e.g White Spirit
Heat resistance	85°C, ISO 4211-3.
Wet scrub resistance	SFS-EN 13300 class II, ISO 11998
Solids volume	Approx. 41 %
Density	Approx. 1.3 kg/l, ISO 2811
Storage	Protect from frost.
Product code	006_5663

APPLICATION DETAILS

Application conditions	During painting and drying, the temperature of the air, surface and paint should be over +5 °C, and the relative humidity of the air below 80 %.
Preparation	Remove dirt and dust from surfaces. Wash the surface with Maalipesu Cleaning Agent according to instructions. Fill holes and cracks with a suitable Presto or Prestonit filler, and sand the dry surface. Remove sanding dust.



Akrostop Stain Blocker

Painting

Stir Akrostop well before use. Apply 1 to 2 coats by brush, roller or spray gun.
Finish with a suitable finishing paint.

Cleaning of tools

Clean tools with water. Tikkurila Pensselipesu (Tool Cleaner) is recommended to be used for cleaning hardened paint from tools.

Maintenance instructions

Earliest 1 month after treatment:

Clean the surfaces with a damp sponge or cloth and with a neutral (pH 6-8) detergent. Thinning instructions of the manufacturer must be followed when mixing the solution.

The surface must not be left wet after cleaning.

After treatment surfaces must be handled with care for a few weeks, because the paint will achieve its final hardness and durability under normal conditions after 1 month.

If surfaces must be cleaned soon after finishing, clean the surface lightly with a damp cloth.

EU VOC 2004/42/EC-limit value

(cat A/g) 30g/l (2010).

Akrostop contains VOC max. 30g/l.

HEALTH AND SAFETY LABELLING

according to Regulation (EC) No. 1272/2008

The product is not classified as dangerous. Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Wear protective gloves. A Material Safety Data Sheet is available on request.

 [Safety data sheet](#)

ENVIRONMENTAL and WASTE DISPOSAL TRANSPORT

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.
VAK/ADR not classified

sre150415 / mli231006 / joa020209 / lko141106 / tho141106 / 006 5663