




Luja Moisture Stop

Description	Waterborne moisture stop which gives a very impervious surface. For interior surfaces treated with Tikkurila Presto LV Humid Room Filler, and on various building boards, glass fibre wallpapers etc.
Product features	Waterproofing gel suitable for application onto bare plaster and mineral board surfaces in areas where high levels of ambient moisture are expected. Luja Moisture Stop forms a completely impervious moisture barrier under Luja finishing coats. Only for use in areas of very high moisture as part of the Luja hygiene system. Luja Moisture Stop is not required where moisture resistant materials exist already.



Recommended uses	Particularly suitable for wet areas of kitchens, bathrooms, shower rooms, utility rooms, swimming pool areas etc.
------------------	---

TECHNICAL DATA



Colour Range	Translucent green.
Coverage	4-6 m ² /l, two coats applied, unthinned. The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method.
Can sizes	3 l
Thinner	Water
Application method	Brush, roller or spray application. Thinning: when necessary, thin with water.
Drying time at 23°C and 50% relative air humidity	Normally touch-dry in 4 hours and recoatable with Luja Finishing Paint after approx. 4 hours.
Solids volume	Approx. 39%
Density	Approx. 1.2 kg/l, ISO 2811
Storage	Protect from frost.
Product code	005_3457

APPLICATION DETAILS

Application conditions	All surfaces to be painted must be dry, the temperature of the air at least +10°C and the relative humidity of the air below 80%.
Preparation	Remove all dirt and dust. If surface to be treated has mould damages, find out the reason for them and repair them carefully before painting. Remove loose, flaking paint with a scraper. Remove vinyl wall coverings and ceramic tiles in full. Sand



Luja Moisture Stop

	glossy paint surfaces to a matt finish. Wash the surface with Maalipesu (Cleaning Agent), if necessary and rinse carefully with water. Fill concrete, plaster etc. surfaces with Presto LV Humid Room Filler. Sand the surface and remove sanding dust.
Surface treatment	Stir Luja Moisture Stop well before use. Apply two coats of moisture stop with a roller and finish off corners and inlets by brush. Allow to dry for 1-4 hours between treatments. Finish with Luja Finishing Paint after approx. 4 hours from the second treatment with moisture stop.
Cleaning of tools	Wash tools with water. Tikkurila Pensselipesu (Tool Cleaner) is recommended for removing slightly hardened paint.
EU VOC 2004/42/EC-limit value	(cat A/i) 140g/l (2010) Luja Moisture Stop contains VOC max. 140g/l.

HEALTH AND SAFETY LABELLING

according to Regulation (EC) No. 1272/2008

The product is not classified as dangerous. A Material Safety Data Sheet is available on request.

 [LUJA KOSTEUSSULKU](#)

ENVIRONMENTAL and WASTE DISPOSAL TRANSPORT

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.
ADR: not classified

ser310816 / linla071114 / inh210604 / pih121015 / 0053457