



Tunto Hieno - Fine Textured Finish

Description	Water-borne acrylate coating.
Product features	Suitable for new or previously painted concrete, screeded surface, brick, wooden fibreboard, gypsum board or chipboard wall surfaces when a textured coating is desired. TUNTO Fine can also be applied on ceilings.
Recommended uses	Walls and ceilings in dry interiors



TECHNICAL DATA



Base paints	AP and C
Colour Range	Can be tinted to the colours of the TUNTO Colour Card. Lighting conditions and surface structure of the product will contribute to the final colour effect. Product must be premixed before tinting.
Gloss grade	Full-matt
Coverage	1-9m ² /l depending on the painting method as follows: <ul style="list-style-type: none">- thick rolling 1-1,5m²/l- thin rolling 4-5 m²/l- brushing 2-2,5m²/l- thick spatula 2-2,5m²/l- thin spatula 7-9m²/l
Can sizes	2.7 l, 9 l.
Thinner	Water
Application method	Apply with roller and for patterning use e.g. a wide brush, wallpaper knife, firm brush or patterning roller. Thinning: With water
Drying time at 23°C and 50% relative air humidity	Re-coatable after 24 hours.
Solids volume	Approx. 53 %.
Density	1.0 kg/l, ISO 2811.
Storage	Protect from frost.
Product code	960_7014

APPLICATION DETAILS

Application conditions	The surface to be treated must be dry, and the temperature of the air, surface and coating must be at least +5° C and the relative humidity of the air below 80 %.
Preparation	Unpainted surfaces: Clean unpainted surfaces from dirt and dust. If necessary, smooth the surfaces with a suitable Presto Light Filler. Prime with Luja Universal Primer. Apply 1-2 coats of Harmony or Nova 7 tinted to the colour of the final product. Previously painted surfaces: Wash down previously painted surfaces with Maalipesu cleaning agent and rinse carefully with water. If necessary, smooth the surfaces with a suitable Presto Filler.



Tunto Hieno - Fine Textured Finish

Painting	<p>Use sandpaper to sand painted glossy surfaces until they are matt and remove the grinding dust. If the colour difference between the substrate and the finish is significant, we recommend to apply one coat of Harmony or Nova 7 tinted to the colour of the final product.</p> <p>Stir TUNTO Fine Textured Finish well before use. Use a roller to apply the product. The surface can be patterned e.g. with a wide brush, wallpaper knife, firm brush or patterning roller. Spread the coating in a thick layer on interior walls approximately one m2 at a time and make the final patterning on the surface immediately. Avoid too thick layers because they may cause the dry surface to crack. For a homogeneous surface reserve enough coating mixed in a single container to avoid possible colour difference.</p>
Filling	<p>If plain paintwork or a different kind of structure surface is wanted, level Tunto surface with suitable Tikkurila Presto filler. Continue treatment from Preparation Unpainted surface.</p>
Cleaning of tools	<p>Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened finish.</p>
Maintenance instructions	<p>Clean surfaces by dry cleaning with a vacuum cleaner, soft brush or dust towel.</p> <p>Handle the surfaces with care after the finishing treatment, as the product achieves the final hardness and durability after approx. one month in normal conditions.</p>

HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

The product is not classified as dangerous. A Safety Data Sheet is available on request.

 [Safety data sheet](#)

ENVIRONMENTAL and WASTE DISPOSAL TRANSPORT

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations. VAK/ADR: not classified

ser040117 / joa100112 / ktu150607 / mkv281016